

## SPLIT TILT

	20' + 4' 15.4K	20' + 4' 17.6K
<b>Model #</b>	P7CAM824DOSTT	P8CAM824DOSTT
<b>GVWR (lb.)</b>	15400	17600
<b>GAWR (lb. / Axle)</b>	7000	8000
<b>Curb Weight</b>	4580	5130
<b>Payload</b>	10820	12470
<b>Main Frame</b>	8" I-Beam @ 10 lbs.	8" I-Beam @ 13 lbs.
<b>Crossmembers</b>	3" Channel	
<b>Side Rail</b>	5" Channel @ 6.7 lb	
<b>Tongue</b>	8" I-Beam @ 10 lbs.	8" I-Beam @ 13 lbs.
<b>Coupler</b>	Adjustable 2-5/16" Ball Coupler	
<b>Jack</b>	12K Bolt-On Drop Leg Jack	
<b>Axles</b>	7,000 lb. Greased	8,000 lb. Oil Bath
<b>Suspension</b>	Slipper Spring Suspension	
<b>Tires</b>	235/80R16 LRE	215/75R17.5 LRH
<b>Wheels</b>	16", 8 on 6.5	17.5", 8 on 6.5
<b>Decking</b>	Pressure-Treated Pine Decking	Oak Decking
<b>Lights</b>	LED Lights - Rubber Mounted	
<b>Electric Plug</b>	7-Way SAE Plug	
<b>Finish</b>	PPG Industrial Polyurethane Paint	
<b>Overall Length</b>	348"	
<b>Deck Height</b>	35"	36"
<b>Coupler Height</b>	20.5" - 29.5"	21.5" - 30.5"
<b>Approach Plate</b>	Knife Edge Approach	
<b>Load Angle</b>	16°	17°

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.

## ADDITIONAL FEATURES

- Safety Chains
- Zip Breakaway System
- Knife Edge Approach
- Rear Impact Guard
- Spare Tire Mount
- D-Ring Tie-Downs - 5/8" (8)
- Stake Pockets and Rub Rail
- Steel Toolbox
- Mud Flaps
- Sealed Wiring Harness
- Power up / Power Down
- Dual Hydraulic Cylinders
- Three Year Warranty

