



DECKOVER TRAILERS


FULL TILT

	22' 15.4K	22' 17.6K	24' 15.4K	24' 17.6K
Model #	P7CAM822DOTT	P8CAM822DOTT	P7CAM824DOTT	P8CAM824DOTT
GVWR (lb.)	15400	17600	15400	17600
GAWR (lb. / Axle)	7000	8000	7000	8000
Curb Weight	4280	4840	4530	5100
Payload	11120	12760	10870	12500
Main Frame	8" I-Beam @ 10 lbs.	8" I-Beam @ 13 lbs.	8" I-Beam @ 10 lbs.	8" I-Beam @ 13 lbs.
Crossmembers	3" Channel		3" Channel	
Side Rail	5" Channel @ 6.7 lb		5" Channel @ 6.7 lb	
Tongue	8" I-Beam @ 10 lb	8" I-Beam @ 13 lb	8" I-Beam @ 10 lb	8" I-Beam @ 13 lb
Coupler	Adjustable 2-5/16" Ball Coupler		Adjustable 2-5/16" Ball Coupler	
Jack	12K Bolt-On Drop Leg Jack		12K Bolt-On Drop Leg Jack	
Axles	7,000 lb. Greased	8,000 lb. Oil Bath	7,000 lb. Greased	8,000 lb. Oil Bath
Suspension	Slipper Spring Suspension		Slipper Spring Suspension	
Tires	235/80R16 LRE	215/75R17.5 LRH	235/80R16 LRE	215/75R17.5 LRH
Wheels	16" Spoke	17.5" Mod	16" Spoke	17.5" Mod
Decking	Pressure-Treated Pine Decking	Oak Decking	Pressure-Treated Pine Decking	Oak Decking
Lights	LED Lights - Rubber Mounted		LED Lights - Rubber Mounted	
Electric Plug	7-Way SAE Plug		7-Way SAE Plug	
Finish	PPG Industrial Polyurethane Paint		PPG Industrial Polyurethane Paint	
Overall Length / Flat	321" / 266"		345" / 290"	
Deck Height	35"	36"	35"	36"
Coupler Height	20.5" - 29.5"	21.5" - 30.5"	20.5" - 29.5"	21.5" - 30.5"
Approach Plate	Knife Edge Approach		Knife Edge Approach	
Load Angle	16°	17°	16°	17°

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.

ADDITIONAL FEATURES

- Steel Plated Tongue
- Safety Chains
- Zip Breakaway System
- Knife Edge Approach
- Rear Impact Guard
- Spare Tire Mount
- D-Ring Tie Downs - 5/8" (6)
- Stake Pockets and Rub Rail
- Steel Toolbox
- Mud Flaps
- Sealed Wiring Harness
- Power up / Power Down
- Dual Hydraulic Cylinders
- Three Year Warranty



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.